


HD Conferencing Camera Brochure


Picture	Model No.	Description	Main Features
Universal HD Camera			
	 520A-HM-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 5X/10X/12X/20X optical Zoom * Interface: HDMI , LAN, RS232 (input)	1080P, 60fps H.265/H.264 Dual Stream Pan/Tilt Rotation: $\pm 170^{\circ}/-30^{\circ}+90^{\circ}$ Pan/Tilt Speed: 60°/sec, 30°/sec. Package: Main Unit, Power supply, IR Controller, USB Cable Dimension: 150X150X167.5(mm) Weight: 1.4KG
	520A-U2-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 5X/10X/12X/20X optical Zoom * Interface: USB2.0 , LAN, RS232, A-IN	
	520A-U3-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 5X/10X/12X/20X optical Zoom * Interface: USB3.0 , LAN, RS232, A-IN	
	520A-ST-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 5X/10X/12X/20X optical Zoom * Interface: HDMI , 3G-SDI , LAN, RS232, RS485 A-IN WIFI (Optional)	
	520A-HD-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 5X/10X/12X/20X optical Zoom * Interface: HDBaseT , LAN, A-IN	
	520A-U2U3-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 5X/10X/12X/20X optical Zoom * Interface: USB2.0 , USB3.0 , HDMI , LAN, RS23	
	960A-ST-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 12X/20X/30X optical Zoom * Interface: 3G-SDI , DVI(HDMI) , LAN, RS232(IN/OUT), A-IN, RS485 WIFI (Optional)	1080P, 60fps H.265/H.264 Dual Stream Pan/Tilt Rotation: $\pm 170^{\circ}/-30^{\circ}+90^{\circ}$ Pan/Tilt Speed: 60°/sec, 30°/sec. Package: Main Unit, Power supply, IR Controller, USB Cable, HDMI Cable Dimension: 285X172X168(mm) Weight: 1.54KG
	960A-U3-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 12X/20X/30X optical Zoom * Interface: USB3.0 , DVI(HDMI) , LAN, RS232(IN)	
	960A-U2U3-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 12X optical Zoom * Interface: USB3.0 、 USB2.0 、 HDMI 、LAN、RS232(IN)、 A-IN	
	610B-MN	* FULL HD Conferencing Camera, 1080P/2MP * Lens: 12X/20X optical Zoom * Interface: HDMI , 3G-SDI , LAN, RS232, RS485, A-IN/OUT, Built in audio pickup * A-OUT by SDI, HDMI * WIFI (Optional)	1080P, 60fps H.265/H.264 Dual Stream Pan/Tilt Rotation: $\pm 170^{\circ}/-30^{\circ}+90^{\circ}$ Pan/Tilt Speed: 100°/sec, 45°/sec. Package: Main Unit, Power supply, IR Controller, RS232 control cable Dimension: 258X172X169(mm) Weight: 1.54KG
	1211S-T20-MN	* FULL HD, HD Conferencing Camera, 1080P/2MP * Lens: 20X Optical Zoom Lens * Interface: HDMI , 3G-SDI , LAN, RS485	1080P, 30/60fps H.264/H.265 Video Compression Dimension: 155.7mmX70mmX70mm Weight: 0.7KG

	1311-MN	<ul style="list-style-type: none"> * FULL HD, HD Conferencing Camera, 1080P/2MP * Lens: 4K Fixed Lens * Interface: 3G-SDI, LAN, RS-485, Audio-in * View Angle: 105° Wide Angle 	<p>1080P, 30/60fps H.264/H.265 Video Compression Dimension: 126.8mmX55mmX58.6mm Weight: 0.5KG</p>
---	---------	---	--


New Version USB Web Camera

	111-MN	<ul style="list-style-type: none"> * FULL HD USB2.0 HD Conferencing Camera, 1080P/2MP * Lens: 4K Lens * Auto Focus * Interface: USB2.0(Power supply and Video out), Built-in Audio. 	<p>1080P, 30fps Mini Size Plug and Play H.264 Video Compression Dimension: 112x65x93mm Weight: 0.25KG</p>
--	--------	--	--

Integrated Endpoint HD Camera

	1070-MN	<ul style="list-style-type: none"> * SIP/H.323 Integrated Endpoint * Lens: 12X optical Zoom * Interface: Audio-IN(XLR, RCA, HDMI), Audio-OUT(RCA, HDMI), Mic-Array In, DVI-IN, HDMI-OUT, USB2.0, LAN, WIFI/4G. * With MCU * Communication Protocol: H.323, SIP. * Video Encoding: H.261, H.263, H.264, H.264HP * Audio Encoding: GG.711A, G.711U, G.722, G.722.1C, G.728, G.729A, AAC-LD * Support Multit-Point Conference 	<p>1080P, 30fps H.264 Dual Stream Pan/Tilt Rotation: ±170°/-30°-+90° Pan/Tilt Speed: 60°/sec, 30°/sec. Dimension:270*184*187mm Weight: 1.94KG</p>
---	---------	---	--

Education Auto Tracking HD Camera

	110-T-MN	<ul style="list-style-type: none"> * FULL HD Conferencing Camera, 1080P/2MP * Lens: 12X20X optical Zoom * Interface: LAN, 3G-SDI, RS-232, A-IN 	<p>1080P, 30/60fps H.264/H.265 Video Compression Pan/Tilt Rotation: ±170°/-30°-+90° Pan/Tilt Speed: 100°/sec, 45°/sec. Dimension: 254mmX144mmX174mm Weight: 1.54KG</p>
	110S-MN	<ul style="list-style-type: none"> * FULL HD Conferencing Camera, 1080P/2MP * Lens: 12X/20X optical Zoom * Interface: LAN, 3G-SDI, RS-232, A-IN 	

Web: www.kvideo.tv Tel: 908-850-1099
Contact: Dave Hartmann Email: dave@hmii.com
See mpeg4 video on our website for demonstration of quality

Universal HD Camera -- 960A-MN



1080P

12X, 20X
Optical Zoom

Video Output:
3G-SDI, HDMI
USB3.0, DVI

RS232, RS485,
Audio-in

Universal HD Camera -- 520A-MN Series

1080P
60fps, 30fps

5X, 10X,
12X, 20X
Optical Zoom

3G-SDI, HDMI
USB3.0, USB2.0
DVI

RS232, RS485,
Audio-in



Universal HD Camera - 550-MN

New Design, ODM Model



1080P
30fps, 60fps

5X, 10X
Optical Zoom
Lens

Video Output:
USB2.0, USB3.0
HDMI, SDI...


RS232, RS485,
Audio-in

Integrated Endpoint -1070-MN

AudioVisual Collaboration Endpoint

SIP/H.323
Protocol

4 in 1 Devices



Integrated Endpoint -1110-MN

1080P
12X Optical Zoom

Android
Platform
For App
Devel.

API/SDK
Open

MIC Built-in



Education HD Camera --110S-MN/110T-MN



1080P

Auto
Tracking

Two
Cameras

Software
Included

Vidyo



Video Conferencing




Clearone



Borderless Education



Distant Learning System



Telemedicine

Main Certifications and Honors 2



China HD Conference Camera Member



Golden Tripod Award



Top 10 Brands In HD Conferencing Video Industry



Top 10 Greatest Brand in China